



PRODUCT SPECIFICATION SHEET

AZOMITE® PELLETIZED



GUARANTEED ANALYSIS

Parameter	Specification
Soluble Potash	0.2%
Calcium	1.8%
Magnesium	0.5%

TYPICAL SPECIFICATIONS

Parameter	Specification
Binder	Magnesium Sulfate
Moisture wt. %	<8%
Bulk Density (loose)	67.50 lb/ft ³ or 1,081.2 kg/m ³
Bulk Density (rodded)	75.4 lb/ft ³ or 1,207 kg/m ³
Size Guide Number (SGN)	280-340
Angle of Repose (degrees)	35 degrees



BENEFITS OF AZOMITE®

- Contains a broad spectrum of over 70 minerals and trace elements.
- AZOMITE® is a natural material that is sized, pelletized or granulated.
- It's 100% natural and completely free from fillers.
- Listed by Organic Materials Review Institute (OMRI) for use in certified organic production.
- Approved California organic input material.
- AZOMITE® is a hydrated sodium calcium aluminosilicate (HSCAS) containing other minerals and trace elements.
- Excellent source of silicon which provides a host soil and plant benefits.

The Safety Data Sheet for this product contains important environmental, health, and safety information regarding this product, including information concerning the handling and storage of this product. Copies of the SDS can be obtained at www.azomite.com or www.azomiteinternational.com or by contacting your AZOMITE® representative.

Effective February 2016 - Specifications are Subject to Change

