

# AZOMITE® MICRONIZED



## GUARANTEED ANALYSIS

Parameter	Specification
Soluble Potash	0.2%
Calcium	1.8%
Magnesium	0.5%

## TYPICAL SPECIFICATIONS

Parameter	Specification
Moisture wt. %	<5%
Bulk Density (loose)	55.99 lb/ft <sup>3</sup> or 896.9 kg/m <sup>3</sup>
Bulk Density (rodded)	57.97 lb/ft <sup>3</sup> or 928.6 kg/m <sup>3</sup>
Size Guide Number (SGN)	<7.5
Angle of Repose (degrees)	40 degrees

## BENEFITS OF AZOMITE®

- AZOMITE® is a natural material that is sized, pelleted or granulated.
- It's 100% natural and completely free from fillers.
- Listed by Organic Materials Review Institute (OMRI) for use in certified organic production.
- Approved California organic input material.
- AZOMITE® is a hydrated sodium calcium aluminosilicate (HSCAS) containing minerals.

The Safety Data Sheet for this product contains important environmental, health, and safety information regarding this product, including information concerning the handling and storage of this product. Copies of the SDS can be obtained at [www.azomite.com](http://www.azomite.com) or [www.azomiteinternational.com](http://www.azomiteinternational.com) or by contacting your AZOMITE® representative.

*This product is not registered for sale in the states of: MS, NM or WI  
Effective January 2017 - Specifications are subject to change*

*Current labels may also include a guarantee for chlorine (Cl) and sodium (Na) at 0.1%. The 10lb bag label may not include the magnesium guarantee as shown above. These may be subject to change.*